




High Frequency Winding Type Chip Inductor GWI0603F-SERIES

1. Features

1. Ceramic core wire wound construction.
2. No batch to batch variations in inductance
3. High Reliability due to ceramic wire wound construction.
4. High frequency application.
5. Small footprint as well as low profile.
6. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
7. Operating temperature-40~+125°C (Including self - temperature rise)



2. Dimensions



Size	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)
GWI0603	1.80 max.	1.20 max.	1.20 max.	0.38 ref.	0.35±0.1

Unit:mm

3. Part Numbering

GWI	0603	F	-	2N0	S
A	B	C		D	E

A: Series
 B: Dimension LxW
 C: Lead free type 2N0=2.0nH
 D: Inductance
 E: Inductance Tolerance C=±0.2nH , S=±0.3nH , J=±5% , K=±10%

4. Specification

Part Number	Inductance (nH)	Tolerance	Test Frequency (Hz)	Q @ 250MHz min.	Rated Current (mA) max.	DCR (Ω) max.	SRF (MHz) min.
GWI0603F-2N0□	2.0	C,S	0.1V/250M	13	700	0.07	8000
GWI0603F-3N9□	3.9	C,S	0.1V/250M	22	700	0.07	6900
GWI0603F-4N7□	4.7	C,J,K	0.1V/250M	20	700	0.12	5800
GWI0603F-6N8□	6.8	C,J,K	0.1V/250M	27	700	0.08	5800
GWI0603F-8N2□	8.2	C,J,K	0.1V/250M	30	700	0.13	4200
GWI0603F-10N□	10	J,K	0.1V/250M	31	700	0.13	4800
GWI0603F-12N□	12	J,K	0.1V/250M	35	700	0.13	4000
GWI0603F-15N□	15	J,K	0.1V/250M	35	700	0.13	4000
GWI0603F-18N□	18	J,K	0.1V/250M	35	700	0.16	3100



Part Number	Inductance (nH)	Tolerance	Test Frequency (Hz)	Q @ 250MHz min.	Rated Current (mA) max.	DCR (Ω) max.	SRF (MHz) min.
GW10603F-22N□	22	J,K	0.1V/250M	38	700	0.23	3000
GW10603F-24N□	24	J,K	0.1V/250M	38	700	0.13	2800
GW10603F-27N□	27	J,K	0.1V/250M	40	600	0.14	2800
GW10603F-33N□	33	J,K	0.1V/250M	40	600	0.22	2300
GW10603F-39N□	39	J,K	0.1V/250M	40	600	0.30	2200
GW10603F-47N□	47	J,K	0.1V/200M	38	600	0.35	2000
GW10603F-56N□	56	J,K	0.1V/200M	38	600	0.37	1900
GW10603F-68N□	68	J,K	0.1V/200M	37	600	0.43	1700
GW10603F-72N□	72	J,K	0.1V/150M	34	400	0.42	1700
GW10603F-82N□	82	J,K	0.1V/150M	34	400	0.71	1700
GW10603F-R10□	100	J,K	0.1V/150M	34	400	0.78	1400
GW10603F-R12□	120	J,K	0.1V/150M	32	300	0.84	1300
GW10603F-R15□	150	J,K	0.1V/150M	28	280	0.96	990
GW10603F-R18□	180	J,K	0.1V/100M	25	240	1.52	990
GW10603F-R22□	220	J,K	0.1V/100M	25	200	2.02	900
GW10603F-R27□	270	J,K	0.1V/100M	24	170	2.36	900
GW10603F-R33□	330	J,K	0.1V/100M	24	185	3.40	700
GW10603F-R39□	390	J,K	0.1V/100M	24	100	3.60	900

