



Winding Type Chip Inductor


GWF2520CF-SERIES

1. Features

1. Ferrite core wire wound construction.
2. High Reliability due to wire wound type construction.
3. Small footprint as well as low profile.
4. Application for DC power line.
5. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
6. Operating temperature-40~+125°C (Including self - temperature rise)



2. Dimensions



Size	A	B	C	D	E
GWF2520	2.90 max.	2.50 max.	2.10 max.	1.20 ref.	0.55±0.1

Unit:mm

3. Part Numbering

GWF	2520	C	F	-	1R0	M
A	B	C	D		E	F

A: Series
 B: Dimension
 C: Application
 D: Lead Free Code
 E: Inductance
 F: Inductance Tolerance

L x W
 DC Power Line
 1R0=1.00 uH
 K = ±10%, M=±20%

4. Specification

Part Number	Inductance (uH)	Tolerance	Test Frequency (Hz)	Q Min.	Test Frequency (MHz)	Rated Current (mA) max.	DCR (Ω) max.	SRF (MHz) min.
GWF2520CF-1R0□	1.00	K,M	0.5V/7.96M	12	7.96	1000	0.13	345
GWF2520CF-1R5□	1.50	K,M	0.5V/7.96M	12	7.96	850	0.17	100
GWF2520CF-2R2□	2.20	K,M	0.5V/7.96M	12	7.96	775	0.21	78
GWF2520CF-3R3□	3.30	K,M	0.5V/7.96M	12	7.96	715	0.26	48
GWF2520CF-4R7□	4.70	K,M	0.5V/7.96M	12	7.96	505	0.52	46
GWF2520CF-6R8□	6.80	K,M	0.5V/7.96M	12	7.96	432	0.72	33
GWF2520CF-8R2□	8.20	K,M	0.5V/2.52M	12	2.52	410	0.76	30
GWF2520CF-100□	10.0	K,M	0.5V/2.52M	12	2.52	392	0.86	28
GWF2520CF-150□	15.0	K,M	0.5V/2.52M	12	2.52	342	1.09	21
GWF2520CF-220□	22.0	K,M	0.5V/2.52M	12	2.52	260	1.96	18
GWF2520CF-330□	33.0	K,M	0.5V/2.52M	12	2.52	236	2.47	15

