



Molding Power Inductor

GMPC1206HP-Series(G)-D

1. Features


1. Carbonyl Powder inductor.
2. Compact design.
3. High current , low DCR , high efficiency.
4. Very low acoustic noise and very low leakage flux noise.
5. High reliability.
6. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
7. Operating temperature -40~+125℃(Including self - temperature rise)




2. Applications

Note PC power system , incl. IMVP-6
DC/DC converter.

3. Dimensions




leadframe



non-leadframe



Recommend PC Board Pattern



Series	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)
GMPC1206HP	13.5±0.5	12.5±0.3	5.7±0.3	2.3±0.3	4.7±0.3

L(mm)	G(mm)	H(mm)
14.2	8.0	5.0

Note: 1. The above PCB layout reference only.
2. Recommend solder paste thickness at 0.15mm and above.

4. Part Numbering

GMPC	1206	HP	-	100	MG	-	D
A	B	C		D	E		F

A: Series

B: Dimension

C: Type

D: Inductance

E: Inductance

F: Code

Tolerance)

BxC

H: Carbonyl Powder ; P: PAD broaden

100=10.0uH

M=±20%

Marking: Black.100 and 1818(20 YY,18 WW, follow production date).



5. Specification

Part Number	Inductance L0 (uH)±20%	I rms (A)Typ	I sat 1 (A)Typ	I sat 2 (A)Typ	DCR (mΩ)Typ. @25℃	DCR (mΩ)Max. @25℃	Type
GMPC1206HP-R22YG-D	0.22±30%	55	100	120	0.48	0.65	non-leadframe
GMPC1206HP-R36MG-D	0.36	42	65	80	0.72	0.90	non-leadframe
GMPC1206HP-R47MG-D	0.47	38	60	64	0.92	1.3	non-leadframe
GMPC1206HP-R56MG-D	0.56	35	56	60	1.15	1.5	non-leadframe
GMPC1206HP-R68MG-D	0.68	33	53	57	1.33	1.7	non-leadframe
GMPC1206HP-R82MG-D	0.82	31	47	55	1.5	1.9	non-leadframe
GMPC1206HP-1R0MG-D	1.00	29	45	53	1.8	2.4	non-leadframe
GMPC1206HP-1R5MG-D	1.50	26	43	50	2.7	3.2	non-leadframe
GMPC1206HP-2R2MG-D	2.20	21	34	43	4.0	4.7	leadframe
GMPC1206HP-3R3MG-D	3.30	17	28	35	5.8	7.1	leadframe
GMPC1206HP-4R7MG-D	4.70	16	25	30	9.5	11.5	leadframe
GMPC1206HP-5R6MG-D	5.60	15.5	22	28	10.8	12.6	leadframe
GMPC1206HP-6R8MG-D	6.80	15	19	25	12	13.8	leadframe
GMPC1206HP-8R2MG-D	8.20	11	17	23	13.6	16	leadframe
GMPC1206HP-100MG-D	10.0	11	15.5	21	18	20.7	leadframe
GMPC1206HP-150MG-D	15.0	9.0	13	16	25	29	leadframe
GMPC1206HP-180MG-D	18.0	8.5	12	15	30	35	leadframe
GMPC1206HP-220MG-D	22.0	8.0	11	14	34	39.5	leadframe
GMPC1206HP-330MG-D	33.0	6.0	8.0	12.0	65	75	leadframe
GMPC1206HP-470MG-D	47.0	5.5	7.0	11.0	80	90	leadframe
GMPC1206HP-680MG-D	68.0	5.0	6.0	9.0	120	140	leadframe

Note:

1. Test frequency : Ls : 100KHz /1.0V.
2. All test data referenced to 25℃ ambient.
3. Testing Instrument(or equ) : L: HP4284A,CH11025,CH3302,CH1320,CH1320S LCR METER / Rdc:CH16502,Agilent33420A MICRO OHMMETER.
4. Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40℃
5. Saturation Current (Isat1) will cause L0 to drop approximately 20%.
Saturation Current (Isat2) will cause L0 to drop approximately 30%.
6. The part temperature (ambient + temp rise) should not exceed 125℃under worst case operating conditions.Circuit design,component,PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
7. Special inquiries besides the above common used types can be met on your requirement.



6. Typical Performance Curves

