



Wire Wound Type Common Mode Filter




GACM3225F2DF-SERIES-D

1. Features


1. High common mode impedance at high frequency effects excellent noise suppression performance.
2. GACM3225F2DF series realizes small size and low profile 3.2x2.5x2.5 mm
3. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
4. Operating temperature -40~+150°C (Including self - temperature rise)



2. Dimension



Recommended PC Board Pattern



Series	A(mm)	B(mm)	C(mm)	D1(mm)	D2(mm)
3225F2DF	3.3±0.2	2.5±0.2	2.5 max	0.55±0.15	0.75±0.20

Units: mm

3. Part Numbering

GACM	3225	F	2	D	F	-	110	T	03	-	D
A	B	C	D	E	F		G	H	I		J

- A: Series
 B: Dimension
 C: Material Ferrite Core
 D: Number of Lines 2=2 lines
 E: Type W4D
 F: Lead free
 G: Inductance 110=11(μH)
 H: Packaging T=Taping and Reel
 I: Rated Current 03=300mA
 J: Control S/N

4. Specification

Part Number	Common mode Impedance (Ω) [10MHz]		Inductance(μH) +50/-30% [100kHz/0.1V]	DC Resistance (Ω) max.	Rated Current (mA) max.	Rated voltage (Vdc) max.	IR (MΩ) min.
GACM3225F2DF-110T03-D	300 min.	550 typ.	11	0.4	300	80	10
GACM3225F2DF-220T02-D	500 min.	1100 typ.	22	0.5	250	80	10
GACM3225F2DF-510T02-D	1000 min.	2600 typ.	51	0.7	200	80	10
GACM3225F2DF-101T01-D	2200 min.	5100 typ.	100	1.5	150	80	10

