



Wire Wound Type Common Mode Filter




GWCM3216F2SF-SERIES

1. Features

1. High common mode impedance at high frequency cause excellent noise suppression performance.
2. GWCM3216F2SF series realizes small size and low profile. 3.2x1.6x2.0 mm.
3. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
4. Operating temperature-40~+125℃ (Including self - temperature rise)




2. Dimension



當破損面積<5%,產品列入允收品範圍

產品破損寬度



Series	A(mm)	B(mm)	C(mm)	D1(mm)	D2(mm)	E(mm)
3216F2SF	3.2±0.2	1.6±0.2	2.0±0.2	0.5±0.1	0.5±0.1	0.15±0.1

Units: mm

3. Part Numbering

GWCM	3216	F	2	S	F	-	900	T	04
A	B	C	D	E	F		G	H	I

- A: Series
 B: Dimension
 C: Material Ferrite Core
 D: Number of Lines 2=2 lines
 E: Type S=Shielded , N=Unshielded
 F: Lead free type
 G: Impedance 900=90Ω
 H: Packaging T=Taping and Reel
 I: Rated Current 04=400mA

4. Specification

Part Number	Common mode Impedance (Ω)	Test Frequency (MHz)	DC Resistance (Ω) max.	Rated Current (mA)max.	Rated Volt. (Vdc)max.	Withstand Volt. (Vdc) Max.	IR (Ω) min.
GWCM3216F2SF-900T04	90±25%	100	0.30	400	50	125	10M
GWCM3216F2SF-121T03	120±25%	100	0.30	350	50	125	10M
GWCM3216F2SF-161T03	160±25%	100	0.40	350	50	125	10M
GWCM3216F2SF-221T03	220±25%	100	0.45	300	50	125	10M
GWCM3216F2SF-261T03	260±25%	100	0.50	300	50	125	10M
GWCM3216F2SF-361T03	360±25%	100	0.60	300	50	125	10M
GWCM3216F2SF-601T03	600±25%	100	0.80	300	50	125	10M
GWCM3216F2SF-102T02	1000±25%	100	1.00	200	50	125	10M
GWCM3216F2SF-222T02	2200±25%	100	1.20	200	50	125	10M



Typical Impedance v.s. Frequency Curve

